


Fast Sensor---RI-29 Series



RI-29 Series


Pico dry-reed switch hermetically sealed in a gas-filled glass envelope. Single-pole, single-throw (SPST) type, having normally open contacts, and containing two magnetically actuated reeds.

The switch is of the double-ended type and may be actuated by an electromagnet, a permanent magnet or a combination of both.

The device is intended for use in relays or similar devices.

RI-29 Series Features

- Can handle up to 20 W load
- Contact layers: gold, copper, sputtered ruthenium
- Superior glass-to-metal seal and blade alignment
- Excellent life expectancy and reliability



General data for all models RI-29

AT-Customization / Preformed Leads

Besides the standard models, customized products can also be supplied offering the following options:

- Operate and release ranges to customer specification
- Cropped and/or preformed leads

Coils

All characteristics are measured using the Philips Standard Coil. For definitions of the Philips Standard Coil, refer to the *Reed Switch Technical & Application Information* Section of this catalog.

Life expectancy and reliability

The life expectancy data given below are valid for a coil energized at 1.25 times the published maximum operate value for each type in the RI-29 series.

No-load conditions (operating frequency: 100 Hz)

Life expectancy: min. 2×10^8 operations with a failure rate of less than 10^{-9} with a confidence level of 90%.

End of life criteria:

- Contact resistance $> 1\Omega$ after 2ms
- Release time > 2 ms (latching or contact sticking).

Loaded conditions (capacitive load: 80 V; 0.1 mA; (700 mA peak); operating frequency: 100 Hz)

RI-29AA

Life expectancy: min. 10^7 operations with a failure rate of less than 2×10^{-8} with a confidence level of 90%.

End of life criterion:

- Release time > 2 ms (latching or contact sticking).

RI-29A

Life expectancy: min. 2×10^7 operations with a failure rate of less than 10^{-8} with a confidence level of 90%.

End of life criterion:

- Release time > 2 ms (latching or contact sticking). Switching different loads involves different life expectancy and reliability data. Further information is available on request.

Mechanical Data

Contact arrangement is normally open; lead finish is tinned; net mass is approximately 100 mg; and can be mounted in any position.

Fast Sensor---RI-29 Series

Model Number			RI-29AA	RI-29A
Parameters	Test Conditions	Units		
Operating Characteristics				
Operate Rangs		AT	16-25	20-34
Release Range		AT	5-18	7-19.5
Operate Time-including bounce (typ.)	(energization)	ms	0.25(31AT)	0.25(42.5AT)
Bounce Time (typ)	(energization)	ms	0.05(31AT)	0.05(42.5AT)
Release Time (mas)	(energization)	us	30(31AT)	30(42.5AT)
Resonant Frequency (typ.)		Hz	6500	6500
Electrical Characteristics				
Switch Power (max)		W	15	20
Switch Voltage DC (max)		V	200	200
Switch Voltage AC ,RMS value (max)		V	140	140
Switch Current DC (max)		mA	1000	1000
Switch Current AC, RMS value (max)		mA	1000	1000
Carry Current DC (max)		A	1.25	1.25
Breakdown Voltage (min)		V	250	280
Contact Resistance (initial max)	(energization)	mΩ	115(25AT)	115(25AT)
Contact Resistance (intial typ.)	(energization)	mΩ	90(25AT)	90(25AT)
Contact Capacitance (max)	without test coil	pF	0.3	0.25
Insulation Resistance (min)	RH≤45%	MΩ	10 ⁶	10 ⁶

Shock

The switches are tested in accordance with “IEC 68-2-27”, test Ea (peak acceleration 150 G, half sinewave; duration 11 ms). Such a shock will not cause an open switch (no magnetic field present) to close, nor a switch kept closed by an 80 AT coil to open.

Vibration

The switches are tested in accordance with “IEC 68-2-6”, test Fc (acceleration 10G; below cross-over frequency 57 to 62 Hz; amplitude 0.75 mm; frequency range 10 to 2000 Hz, duration 90 minutes in each direction).Such a vibration will not cause an open switch (no magnetic field present) to close, nor a switch kept closed by an 80 AT coil to open.

Mechanical Strength

The robustness of the terminations is tested in accordance with “IEC 68-2-2P”, test Ua (load 10N).

Operating and Storage Temperature

Operating ambient temperature; min: -55°C; max: +75°C. Storage temperature; min: -55°C; max: +125°C. Note: Temperature excursions up to 150°C

may be permissible. For more information contact your nearest Coto Technology sales office.

Soldering

The switch can withstand soldering heat in accordance with “IEC 68-2-20”, test Tb, method 1B: solder bath at 350±10°C for 3.5±0.5 s. Solderability is tested in accordance with “IEC 68-2-20”, test Ta, method 3: solder globule temperature 235°C; ageing 1b: 4 hours steam.

Welding

The leads can be welded.

Mounting

The leads should not be bent closer than 1 mm to the glass-to-metal seals. Stress on the seals should be avoided. Care must be taken to prevent stray magnetic fields from influencing the operating and measuring conditions.